Motormower : MF 90 MF 90 50S





Features

- >Professional cast iron engine warranted 3 years or 2500 h.
- >Dead man's handle safety lever on handlebar.
- >Independent clutch for cutting bar.
- >Height of cut adjustable with skids.
- >Minimum cutting height: 3 cm.
- >Mechanism with kinetic cone.
- >350 mm diameter tractor wheels run flat treated.
- >Coverage 1500 m2 per hour on open land.
- >Oscillating ESM bar (87 cm) with self adjusting mechanism between the blade and the fingers.
- >Foldable handlebars on silent blocks.
- >3/4 turn hubs for improved handling.

Technical information

Recommended area < 5 000 M²
Working width 87 cm
Gears Single speed: 2,5 km/h
Weight 73 kg
Type of engine Subaru EP 16

4 stroke cycle OHC

Displacement 169 cm³

Net power output ¹ 4,2 kW at 4000 rpm-1 Nominal power output 3,3 kW at 3300 rpm-1

Fuel capacity 3,4 L Oil capacity 0,6 L

Practical information

Packaging Unit box Box dimensions 1200 x 800 (Lxlxh) x 1000 mm Quantity by pallet Туре Mower Pallet dimensions 1200 x 800 (Lxlxh) x 2000 mm Product code 0000030206 Gen Code 3700304807127

For accessories or options please contact us or visit our website www.pubert.com

¹ The Engine power output indicated in this document is a net value measured by testing a motor according to the SAE J 1349 norm at a given engine revolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine revolution speed, temprature, humidity, atmospheric pressure, maintenance and others.

