

# Scarifier : Oscar Pro OSCAR PRO 55H



## Features

- › Professional cast iron engine with oil bath air filter.
- › 28 foldable blades in double row.
- › Independant lever for lowering rotor to the ground.
- › Front wheel and rear wheel, with bearing and metal rims.
- › Dead-man's handle for rotor clutch on handlebar.
- › Working depth adjustable by thumb-wheel.
- › Foldable and adjustable Handlebar : 2 positions.
- › Rotor assembled on bearings with cast iron flange and grease fittings.

## Technical information

Recommended area	5 000 M <sup>2</sup>
Working width	50 cm
Working depth	0-1,5 cm
Wheels	Forward Ø 210 mm Reverse Ø 250 mm
Weight	65 kg
Type of engine	Honda GX160 4 stroke cycle OHV
Displacement	163 cm <sup>3</sup>
Net power <sup>1</sup>	3,6 kW at 3600 rpm-1
Nominal power	3,5 kW at 3300 rpm-1
Fuel capacity	3,6 L
Oil capacity	0,6 L

## Practical information

Packaging	Carton box
Box dimensions (Lxlxh)	800 x 840 x 880 mm
Quantity by pallet	3
Pallet dimensions (Lxlxh)	800 x 860 x 2600 cm
Product code	0000020202
Gen Code	3700304807028

For accessories or options please contact us  
or visit our website [www.pubert.fr](http://www.pubert.fr)

<sup>1</sup> The Engine power output indicated in this document is a net value measured by testing a motor according to the SAE J 1349 norm at a given engine revolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine revolution speed, temperature, humidity, atmospheric pressure, maintenance and others.

<sup>1</sup> The Engine power output indicated in this document is a net value measured by testing a motor according to the SAE J 1349 norm at a given engine revolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine revolution speed, temperature, humidity, atmospheric pressure, maintenance and others.