## Tiller: Ecomax ECOMAX 50S C2





## **Features**

- > 6 dismountable forged tines (straight riveted knives) + discs
- > Height and offset adjustable handlebar
- > Transmission by chain, dismountable and greased
- > Waterproof seals on transmission shaft Ø 25mm
- > Mechanical reverse gear with inversion control on handlebar
- > Belt tension clutch
- > Spur
- > Foldable front wheel

## **Technical information**

 Recomended area
 < 1000 m²</td>

 Working width
 40 / 60 / 80 cm

 Gears
 1 forward (120 rpm)

1 reverse

Working tools 6 tines Ø 320 mm

Weight 54 kg
Engine Subaru EP16
Displacement 169 cc

Net power<sup>1</sup> 4,2 KW to 4000 rpm Nominal power 3,3 KW to 3300 rpm

Fuel tank capacity 3,4 L Oil tank apacity 0,6 L

## **Practical information**

Packaging Carton box

Box dimensions (Lxlxh) 830 x 600 x 820 mm

Quantity per pallet 12

 Pallet dimensions
 1650 x 1200

 (Lxlxh)
 x 2630 mm

 Product code
 3000022302

Gen Code 3700304800609

For accessories or options please contact us or visit our website www.pubert.com

<sup>1</sup> The Engine power output indicated in this document is a net value measured by testing a motor according to the SAEJ1349 norm at a given enginer evolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine evolution speed, temperature, humidity, atmospheric pressure, maintenance and others.

reserve the right to change the design, specifications and attachements of the models presented, without notice. All products with moving parts can be dangerous if used correctly. For this reason you should Pubert S.A. are constantly stiving to improve the quality of their products, and

always read the instructions carefully