Light tillers: Nano NANO 40B





Features

- > 6 dismountable forged tines (straight riveted knives)
- > Foldable and height adjustable handlebar
- > Transmission by chain, dismountable and greased
- > Versatile tiller which can be used with accessories
- > Belt tension clutch
- > Transmission shaft Ø 20 mm
- > Double rear transport wheel

Technical information

Recomended area $< 500 \text{ m}^2$ Working width 20 / 30 / 46 cm 1 forward (160 rpm) Gears Working tools 6 tines Ø 240 mm 26 kg

Weight

Briggs & Stratton Engine

550 series

Displacement 127 cc

2,39 KW to 3600 rpm Net power¹ Nominal power 2,3 KW to 3150 rpm

Fuel tank capacity 2 L

Practical information

Carton box

Box dimensions (Lxlxh) 650 x 460 x 510 mm

Quantity per pallet 16 Pallet dimensions

1350 x 950

(Lxlxh)

x 2180 mm

Product code Gen Code

6000020502

3700304803112

For accessories or options please contact us or visit our website www.pubert.com

¹ The Engine power output indicated in this document is a net value measured by testing a motor according to the SAEJ1349 norm at a given enginer evolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine evolution speed, temperature, humidity, atmospheric pressure, maintenance and others.