

Tiller : Elite ELITE PRO 55HC



Features

- > Professional cast iron engine, warranted 3 years or 2500 hours
- > 6 dismountable forged tines (helicoïdal riveted knives) + discs
- > Soft pneumatic clutch, enables to increase the belt lifetime, unequalled using comfort
- > Height and offset adjustable handlebar with only one lever
- > Transmission by chain, dismountable and greased
- > Heavy-duty transmission with double-walled steel housing
- > Waterproof seals on transmission shaft Ø 25 mm
- > «Soft grip» handles
- > Mechanical reverse gear with inversion control on handlebar
- > Belt tension clutch
- > Adjustable spur
- > Foldable front wheel

Technical information

Recommended area	< 2500 m ²
Working width	40 / 60 / 80 cm
Gears	1 forward (120 rpm)
Working tools	6 tines Ø 320 mm
Weight	57 kg
Engine	Honda GX160
Displacement	163 cc
Net power ¹	3,6 KW to 3600 rpm
Nominal power	3,5 KW to 3300 rpm
Fuel tank capacity	3,1 L
Oil tank capacity	0,6 L

Practical information

Packaging	Carton box
Box dimensions (Lxhx)	830 x 600 x 820 mm
Quantity per pallet	12
Pallet dimensions (Lxhx)	1650 x 1200 x 2630 mm
Product code	3000022501
Gen code	3700304810479

For accessories or options please contact us or visit our website www.pubert.com

¹ The Engine power output indicated in this document is a net value measured by testing a motor according to the SAEJ1349 norm at a given engine evolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine evolution speed, temperature, humidity, atmospheric pressure, maintenance and others.

