Convertible tiller: Quatro Junior Q JUNIOR 60H





Features

- > Honda cast iron engine, with dual element air filter
- > 4, monobloc, forged steel tines
 - + 2 additional tines (ploughing riveted blades) + discs
- > Reinforced chassis
- > Adjustable height and floated handlebar with only one lever
- > Mechanical gearbox Steel housing - Lubrification with oil
- > Waterproof seals on transmission shaft on blade spindle Ø25 mm
- > Belt tension clutch
- > Adjustable spur
- > Retractable front wheel

Technical information

Recomended area < 2 500 m²
Working width 60 / 90 cm
Gears 2 forward

35 - 120 rpm-1 1 reverse

Working tools 6 tines Ø 325 mm

Weight 76 kg
Engine Honda GP200
Displacement 200 cc

Net power¹ 4,1 KW to 3600 rpm Nominal power 3,9 KW to 3300 rpm

Fuel tank capacity 3,1 L Oil tank apacity 0,6 L

Practical information

Packaging Carton box
Box dimensions (Lxlxh) 830 x 600 x 820 mm
Quantity per pallet 12

 Pallet dimensions
 1650 x 1200

 (Lxlxh)
 x 2630 mm

 Produc code
 3500020704

 Gen code
 3700304801354

For accessories or options please contact us or visit our website www.pubert.com

¹ The Engine power output indicated in this document is a net value measured by testing a motor according to the SAE11349 norm at a given enginer evolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine evolution speed, temperature, humidity, atmospheric pressure, maintenance and others.



models presented, without notice. All products with moving parts can be dangerous if used correctly. For this reason you should always read the instructions carefully reserve the right to change the design, specifications and attachements of the Pubert S.A. are constantly stiving to improve the quality of their products, and