

# Convertible tiller: Quatro Senior Q SENIOR 65H D



## Features

- > Honda cast iron engine, with oil bath air filter
- > Remote engine switch-button
- > 4, monobloc, forged steel tines + 2 additional tines (ploughing riveted blades) + discs
- > Reinforced chassis
- > Adjustable height and floated handlebar with only one lever
- > Double protection at the bottom of the transmission
- > Mechanical gearbox - Steel housings - Lubrification with oil
- > Waterproof seals on transmission shaft Ø 30 mm
- > Belt tension clutch
- > Blade disconnection integrated and independant on each wheel
- > Adjustable spur
- > Foldable front wheel

## Technical information

Recommended area	< 5 000 m <sup>2</sup>
Working width	60 / 90 cm
Gears	3 forward 40-75-130 rpm-1 1 reverse
Working tools	6 tines Ø 325 mm + discs
Weight	82 kg
Engine	Honda GX 200 4 temps OHV
Displacement	196 cc
Net power <sup>1</sup>	4,1 KW to 3600 rpm
Nominal power	4 KW to 3450 rpm
Fuel tank capacity	3,6 L
Oil tank apacity	0,6 L

## Practical information

Packaging	Carton box
Box dimensions (Lxlxh)	830 x 600 x 820 mm
Quantity per pallet	12
Pallet dimensions (Lxlxh)	1650 x 1200 x 2630 mm
Produc code	3500020206
Gen code	3700304801040

For accessories or options please contact us  
or visit our website [www.pubert.com](http://www.pubert.com)

<sup>1</sup> The Engine power output indicated in this document is a net value measured by testing a motor according to the SAEJ1349 norm at a given engine evolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine evolution speed, temperature, humidity, atmospheric pressure, maintenance and others.