

Wheeled brushcutter: Xtrem XTREM 12 60S



Features:

- › «Dead man's handle » on handlebar.
- › Starter on handlebar.
- › Belt tension clutch + 6 speed Gearbox.
- › Height and lateral adjustable handlebar with only one lever.
- › Ergonomic controls and handles.
- › Steel cutting cover 53 cm.
- › Removable front and side deflectors.
- › Stringy plant cutting on blade hub.
- › Dismountable and independent 3rd main bearing for a good crankshaft protection.
- › Free wheels, rotates 360°.
- › Inspection hatch at the cover back.
- › Centralized cutting height control: 4 positions.
- › Rear wheels on ball bearings
- › Swiveling metallic front wheel (possible fixed position).
- › Grinding blade : "mulshing" type.

Technical information

Recommended area	< 4 000 m ²
Working width	51 cm
Gears	from 2,0 to 4,2 km/h
Cutting height	110-90-70-50 mm
Wheels	Front: Ø 200 mm Rear: Ø 370 mm
Weight	62 kg
Type of engine	Subaru EA 190V 4 stroke cycle OHC
Displacement	189 cm ³
Net power output ¹	4,1 kW at 3600 rpm-1
Nominal power output	3,4 kW at 3200 rpm-1
Fuel capacity	1,0 L
Oil capacity	0,6 L

Practical information

Packaging	Unit box
Box dimensions (LxHxh)	1160 x 600 x 660 mm
Quantity by pallet	6
Pallet dimensions (LxHxh)	1200 x 1200 x 2100 mm
Product code	4000200804
Gen Code	3700304802238

For accessories or options please contact us
or visit our website www.pubert.fr

¹ The Engine power output indicated in this document is a net value measured by testing a motor according to the SAE J 1349 norm at a given engine revolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine revolution speed, temperature, humidity, atmospheric pressure, maintenance and others.

