

Wheeled brushcutter: Xtrem XTREM 12 60SM



Features

- > «Dead man's handle » on handlebar.
- > Starter on handlebar.
- > Belt tension clutch
+ 6 speed Gearbox.
- > Height and lateral adjustable handlebar with only one lever.
- > Ergonomic controls and handles.
- > Steel cutting cover 53 cm.
- > Removable front and side deflectors.
- > Stringy plant cutting on blade hub.
- > Dismountable and independent 3rd main bearing for a good crankshaft protection.
- > Wheels with differential :
"Special mountain".
- > Inspection hatch at the cover back.
- > Centralized cutting height control:
4 positions.
- > Rear wheels on ball bearings.
- > Swiveling metallic front wheel
(possible fixed position).
- > Grinding blade : "mulshing" type.

Technical information

Recommended area	< 4 000 m ²
Working width	51 cm
Gears	from 2,0 to 4,2 km/h
Cutting height	110-90-70-50 mm
Wheels	Front: Ø 200 mm Rear: Ø 370 mm
Weight	62 kg
Type of engine	Subaru EA 190V 4 stroke cycle OHC
Displacement	189 cm ³
Net power output ¹	4,1 kW at 3600 rpm-1
Nominal power output	3,4 kW at 3200 rpm-1
Fuel capacity	1,0 L
Oil capacity	0,6 L

Practical information

Packaging	Unit box
Box dimensions (LxHxh)	1160 x 600 x 660 mm
Quantity by pallet	6
Type	Motor-crushing grinding with pedestrian control
Pallet dimensions (LxHxh)	1200 x 1200 x 2100 mm
Product code	4000200805
Gen Code	3700304802245

For accessories or options please contact us
or visit our website www.pubert.fr

¹ The Engine power output indicated in this document is a net value measured by testing a motor according to the SAE J 1349 norm at a given engine revolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine revolution speed, temperature, humidity, atmospheric pressure, maintenance and others.

