

Wheeled brushcutter: Xtrem XTREM 12 65H



Features

- > « Dead man's handle » on handlebar.
- > Starter on handlebar.
- > Belt tension clutch + 6 speed Gearbox.
- > Height and lateral adjustable handlebar with only one lever.
- > Ergonomic controls and handles.
- > Steel cutting cover 53 cm.
- > Removable front and side deflectors.
- > Stringy plant cutting on blade hub.
- > Dismountable and independent 3rd main bearing for a good crankshaft protection.
- > Free wheels, rotates 360°.
- > Inspection hatch at the cover back.
- > Centralized cutting height control: 4 positions.
- > Rear wheels on ball bearings.
- > Swiveling metallic front wheel (possible fixed position).
- > Grinding blade : "mulshing" type.

Technical information

Recommended area	< 4 000 m ²
Working width	51 cm
Gears	from 1,9 to 3,9 km/h
Cutting height	110-90-70-50 mm
Wheels	Front: Ø 200 mm Rear: Ø 370 mm
Weight	62 kg
Type of engine	Honda GCV 190 4 stroke cycle OHC
Displacement	189 cm ³
Net power output ¹	3,4 kW at 2900 rpm-1
Nominal power output	3,8 kW at 3600 rpm-1
Fuel capacity	1,1 L
Oil capacity	0,55 L

Practical information

Packaging	Unit box
Box dimensions (LxHxh)	1160 x 600 x 660 mm
Quantity by pallet	6
Pallet dimensions (LxHxh)	1200 x 1200 x 2100 mm
Product code	4000200803
Gen Code	3700304802252

¹ The Engine power output indicated in this document is a net value measured by testing a motor according to the SAE J 1349 norm at a given engine revolution speed. The power of another motor may be different from the indicated value. The true power of a motor depends on several factors such as engine revolution speed, temperature, humidity, atmospheric pressure, maintenance and others.

For accessories or options please contact us
or visit our website www.pubert.fr



PUBERT S.A.S. · Z.I. de Pierre-Brune · B.P. 25 · 85111 Chantonay Cedex · France
Tél. 02 51 45 81 81 · Fax. 02 51 94 37 00 · Web : www.pubert.fr · E-Mail : contact.commercial@pubert.fr